

# ECS4510-12PD

## L2 Gigabit Ethernet PD PSE Switch



### Product Overview

The Edge-Core ECS4510-12PD is a Layer 2 Gigabit Ethernet PD PSE switch featuring 12 ports; with 8 10/100/1000BASE-TX PoE PD ports, 2 Gigabit Ethernet ports, and 2 Gigabit fiber SFP ports. The ECS4510-12PD is compliant with IEEE 802.3at as a PoE Power Device (PD) on ports 1 to 8, and as an IEEE 802.3af-compliant PoE Power Sourcing Equipment (PSE) device on port 10. The ECS4510-12PD is designed to support wireless, IP video, and other applications for the retail and enterprise customer. This switch is packed with features and is a cost-effective solution that brings continuous availability, enhanced security, and advanced QoS to the network edge, while maintaining simplicity of management.

### Key Features and Benefits Performance and Scalability

The ECS4510-12PD is a high-performance Gigabit Ethernet Layer 2 managed switch with 24 Gbps switching capacity. It delivers wire-speed switching performance on all Gigabit ports, allowing users to take full advantage of existing high-performance Gigabit integrated servers and PCs by significantly improving the responsiveness of applications and file transfer times.

The device also has two Gigabit Ethernet (RJ-45 and SFP) ports, providing the flexibility of copper or fiber high-speed uplinks to servers or the network backbone. This switch also supports digital diagnostic monitoring (DDM) for SFP transceivers.

### Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol provides a loop-free network and redundant links to the core network with rapid convergence, ensuring a faster recovery from failed links and enhancing overall network stability and reliability.

IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base, providing Layer 2 load sharing on redundant links for up to 16 instances.

The ECS4510-12PD supports IEEE 802.3ad Link Aggregation Control Protocol (LACP). It increases bandwidth by automatically aggregating several physical links together as a logical trunk and offers load balancing and fault tolerance for uplink connections.

### Comprehensive QoS

The ECS4510-12PD offers advanced QoS for marking, classification, and scheduling to deliver best-in-class performance for data, voice, and video traffic at wire speed. Four egress queues per port enable differentiated management of up to four traffic types through the switch.

Traffic is prioritized according to 802.1p and DSCP to provide optimal performance for real-time applications. Weighted Round Robin (WRR) and strict priority ensure differential prioritization of packet flows and avoid congestion of ingress and egress queues.

Asymmetric bidirectional rate-limiting, per port or per traffic class, preserves network bandwidth and allows maximum control of network resources.

### Key Features and Benefits Enhanced Security

Port Security limits the total number of devices from using a switch port and protects against MAC flooding attacks.

IEEE 802.1X port-based or MAC-based access control ensures all users are authorized before being granted access to the network. When a user is authenticated, the VLAN, QoS, and security policy are automatically applied to the port where the user is connected, otherwise the user is grouped in a guest VLAN with limited access.

DHCP snooping allows a switch to protect a network from rogue DHCP servers that offer invalid IP addresses.

Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on source and destination MAC addresses, IP addresses, or TCP/UDP ports. ACLs are hardware supported, so switching performance is not compromised.

Secure Shell (SSHv1.5/v2.0) and Secure Sockets Layer (SSL/HTTPS) encrypt Telnet and web access to the switch, providing secure network management.

Radius/TACACS+ Authentication, the ECS4510-12PD support both RADIUS /TACACS+ authentication methods to secure your network.

### Simple Management

An industry-standard command-line interface (CLI), accessed through the console port or Telnet, provides a familiar user interface and command set for users to manage the switch.

### PD and PSE Feature

The ECS4510-12PD supports PoE as a Powered Device (PD) and is compliant with IEEE 802.3at. Copper ports 1 to 8 can receive 48 VDC primary power supplied by a PSE device.

Port 10 serves as a PoE PSE port and is compliant with IEEE 802.3af. This feature is enabled only when the switch is powered from at least one 802.3at PSE source or from the AC power adapter.

## Features

### Physical Ports

- 8 Gigabit Ethernet RJ-45 ports (ports 1~8)
- 2 Gigabit Ethernet RJ-45 uplink ports (ports 9~10)
- 2 Gigabit SFP ports for fiber uplinks (ports 11~12)
- Ports 1~ 8 support PoE as a powered device compliant with 802.3af
- Port 10 supports PoE as power sourcing equipment compliant with 802.3af
- 1 RJ-45 console port

### Performance

- Switching Capability: 24 Gbps
- Forwarding Rate: 17.9 Mpps
- MAC Address Table: 16 K
- Flash: 32 MByte
- SDRAM: 128 MByte

### L2 Features

- Auto-negotiation for port speed and duplex mode
- Flow Control:
  - IEEE 802.3x for full-duplex mode
  - Back-pressure for half-duplex mode
- Spanning Tree Protocol:
  - IEEE 802.1D Spanning Tree Protocol (STP)
  - IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
  - IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
  - BPDU Guard
  - BPDU filtering
  - Root Guard
- Vlans:
  - Supports 4K IEEE 802.1Q VLANs
  - Port-based VLANs
  - GVRP
  - Mac-based VLANs
  - Private VLAN (Traffic Segmentation per port)
  - Support Q-in-Q
  - Support MVR
- Link Aggregation:
  - Static Trunk
  - IEEE 802.3ad Link Aggregation Control Protocol
  - 2~8 port/trunk
  - Up to 6 trunk groups
- IGMP Snooping:
  - IGMP v1/v2/v3 snooping
  - IGMP Proxy
  - IGMP Filtering
  - IGMP Throttling
  - IGMP Immediate Leave
- Supports jumbo frames up to 10 K

### QoS Features

- Priority Queues: 4 hardware queues per port
- Traffic classification based on IEEE 802.1p CoS, IP Precedence, DSCP, TCP/UDP port number
- Supports WRR and Strict scheduling
- Rate Limiting (Ingress and per port base)
- DiffServ Marking/Remarking

### IPv6 Features

- IPv4/IPv6 dual protocol stack
- IPv6 Address Type Stack: Unicast
- IPv6 Neighbor Discovery
- Stateless auto configuration
- Manual configuration
- SNMP over IPv6
- HTTP over IPv6
- SSH over IPv6
- IPv6 Telnet
- IPv6 DNS Resolver
- IPv6 Syslog
- IPv6 SNTP
- IPv6 TFTP Remote
- IPv6 ACL

### Security Features

- User/Password protected system management terminal (Telnet, Web)
- Support L2/L3/L4 access control list (512 rules, extended mode 256 rules.)
- RADIUS AAA
- TACACS AAA
- TACACS+3.0
- SSH v1.5/v2.0(Secured Telnet session)
- HTTPS/SSL
- IEEE 802.1x port-based security
- MAC Based Authentication
- IP source guard
- Security(drop or copy) for multiple packet types
- Ethernet Type II
- IEEE 802.1q
- MAC address
- SA/DA MAC address
- IEEE 802.1p /D priority
- Ethernet type field
- TCP/UDP port numbers
- SA/DA IP address
- Protocol
- EXTented Ipv6 ACL

### Management

- Switch Management:
  - CLI via console port or Telnet
  - Web management
  - SNMP v1, v2, v3
- Firmware and Configuration:
  - Firmware upgrade via TFTP server
  - Supports dual image
  - Supports auto configuration provision
  - Supports auto firmware upgrade
  - Multiple configuration files
  - Configuration file upload/download via TFTP server
- Supports RMON (groups 1, 2, 3 and 9)
- Supports BOOTP, DHCP client for IP address assignment
- Supports DHCP snooping
- Supports SNTP (RFC 2030)
- Supports IP clustering up to 36 switches
- Event/error log, Syslog
- Support Public and private MIB
- Supports LLDP (802.1ab)
- Supports IPv6 management

## Features

### Power Supply

- DC Power Input
  - 48 VDC, 0.65 A

### Mechanical

- Dimensions: 180 x 165 x 37.5 (mm) (W x D x H)
- Weight: 0.69 kg (1.52 lb)
- 19" Rack Space

### Safety

- UL 60950-1 CB (IEC60950-1)

### Electromagnetic Compatibility

- CE Mark
- FCC Class A
- EN55022 (CISPR22) Class A

### Environmental Specifications

- Temperature:
  - 0° C to 50° C (standard operating)
  - -40° C to 70° C (non-operating)
- Operating Humidity: 10% to 90% (non-condensing)
- Storage Humidity: 10% to 90% (non-condensing)

### IEEE Standards

- IEEE 802.3 10BASE-T [1]
- IEEE 802.3u 100BASE-TX and 100BASE-FX [2]
- IEEE 802.3x flow control Supports
- IEEE 802.1D (Bridging), 1993
- IEEE 802.1Q (Virtual LAN) 1998
- IEEE 802.1x, port-based network access control, 2001

### Warranty

- Please check [www.edge-core.com](http://www.edge-core.com) for the warranty terms in your country.

### For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit [www.edge-core.com](http://www.edge-core.com).

### About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at [www.edge-core.com](http://www.edge-core.com).

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore Data Center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2017 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

## Ordering Information

Optional Accessories	Product Description
ET4201-SX	1Gbps, Small Form Factor Pluggable (Distance: 500 m; Wavelength: 850nm)
ET4201-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)
ET4201-LHX	1Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1310 nm)
ET4201-ZX	1Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm)
ET4202-SX	1Gbps, Small Form Factor Pluggable (Distance: 500 m; Wavelength: 850 nm, DDM)
ET4202-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310nm, DDM)
ECView Pro	SNMP Network Management Software